

Certificate of Express Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service by Express Mail in an envelope addressed to: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date indicated below.

Express Mail Label No.: EV349882825US

Date: November 12, 2003

Signature: Vanessa Lake

**APPLICATION FOR LETTERS PATENT
UNITED STATES OF AMERICA**

Be it known that we, **Iñigo LIZARRALDE**, residing at Ibargaray Street 42, 3rd Floor, Bergara, Spain; and **Julian ECHEBERRIA**, residing at Wenceslao Orbea Street 18, 3rd Floor, Eibar, Spain, citizens of Spain, have invented certain new and useful improvements in a

MUZZLE-LOADING FIREARM WITH PIVOTING BLOCK ACTION

for which the following is a specification.

**GARDNER GROFF, P.C.
Paper Mill Village, Building 23
600 Village Trace, Suite 300
Marietta, Georgia 30067
770.984.2300**

MUZZLE-LOADING FIREARM WITH PIVOTING BLOCK ACTION**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] The present application claims the priority benefit of U.S. Provisional Patent Application Serial No. 60/425,950, filed November 12, 2002; U.S. Provisional Patent Application Serial No. 60/443,936 filed January 31, 2003; and U.S. Provisional Patent Application Serial No. 60/497,420, filed August 22, 2003; all of which are hereby incorporated herein by reference in their entireties.

TECHNICAL FIELD

[0002] The present invention relates to a firing mechanism for a muzzle-loading firearm, such as a muzzle-loading rifle, shotgun, cannon or the like. This invention relates more specifically toward a pivoting block firing mechanism for a muzzle-loader.

BACKGROUND OF THE INVENTION

[0003] In the second half of the 19th century, cartridge style rifles became popular and the market for older muzzle-loading designs started to wane. After the introduction of the cartridge style rifle, which fires a pre-assembled cartridge or bullet, firearm manufacturers started developing movable firing mechanisms (movable blocks) to provide access to the firing chamber for replacing a spent cartridge with a fresh one. Eventually, cartridge style rifles were developed with "bolt action" to speed movement of a cartridge into the firing chamber and ultimately repeating rifles were developed that used the explosive power unleashed from the firing of the cartridge itself to remove the spent shell. These developments effectively obviated the need for movable block actions in cartridge style firearms. Meanwhile, developments in the older, outdated muzzle-loading firearms slowed as the muzzle-loading firearms fell out of favor. Not surprisingly, it does not appear that the movable firing mechanisms used in 19th century cartridge style firearms were ever adapted to muzzle-loading firearms before the muzzle-loading firearm all but disappeared from manufacture. Now that muzzle-loading firearms have experienced a resurgence in popularity, there is a need for a

muzzle-loading firearm that includes a movable firing mechanism to provide convenient access to the breech, as will be explained below.

[0004] Hunting with muzzle-loading firearms has become increasingly popular in recent years. Perhaps one of the reasons for this popularity is that some people enjoy manually loading the powder and projectile into the muzzle, and then packing it with the ramrod. As evidence of the increasing popularity of muzzle-loading firearms, some states within the United States have separate hunting seasons for sportsmen using muzzle-loading firearms. Despite their recent increased popularity, muzzle-loading firearms have presented several problems to those that use them.

[0005] The muzzle-loading firearms used for hunting can be divided into two major groups. First is the traditional type, which normally is made with the firing mechanism positioned to one side of the barrel. And second is the "in-line" type, which is made to have the firing mechanism "in-line" and includes an ignition system directly behind the barrel, which therefore is substantially "lined up" with the barrel. Both of these types of firearms typically include a barrel, a trigger positioned within a trigger guard, a hammer, a striker, and their corresponding springs.

[0006] However, whether they are traditional or in-line, these firearms typically have problems in common. Such deficiencies of the firearms include the following:

- **Excessive Residue:** The black powder that is used in shooting these firearms typically leaves residue on both the barrel and the firing mechanisms. Therefore, these firearms must be disassembled and cleaned periodically. This disassembly is difficult and time-consuming, and obtaining an acceptable cleaning result without disassembling all, or a substantial part, of the firearm is very difficult. Additionally, the traditional type of muzzle-loading firearms are even more difficult to clean, making the residue problem even more severe.
- **Blowback Gas Injuries:** Shooting muzzle-loading firearms often causes "blowback gas." This gas, which is a byproduct of the burning of the black

powder, can cause injury and burns to the shooter. Typically, the traditional models are safer than the "in-line" ones, as the gas outlet of a traditional model is located to one side of, instead of directly aligned with, the face of the user. However, traditional models face a problem when a left-handed shooter uses a firearm intended to be for a right-handed person.

- Loading Time: The loading time, which includes the time for replacement of the percussion cap, reloading the powder and the bullet and compressing them, is significantly long. This problem is typically worse for in-line models, as access for reloading the percussion caps or other form of primers is very difficult and a user typically must use a special tool for this purpose.
- Barrel Length: Because of the type of powder used, these types of firearms typically have relatively long barrels, making them rather heavy.

[0007] In-line muzzle-loading rifles were introduced to the marketplace in recent years to address the cleaning difficulties and the lack of reliability and precision often encountered in traditional muzzle-loaders. The precision of the rifle is typically inversely proportional to the time it takes to shoot, considering the shooting time as the time it takes from when the trigger is pulled until the powder, that expels the bullet, explodes.

[0008] As previously discussed, previously known in-line rifles have problems with regard to the blowback gas and with the long reloading times. Additionally, this type of rifle also has another disadvantage in comparison to traditional muzzle-loading rifles, as they often have a longer overall length for a given effective barrel length (i.e., the length of the bore into which the powder charge and bullet are loaded), because the firing mechanism and primer loading action are located behind the barrel (rather than beside it), and similarly may also have a greater weight for a given effective barrel length than traditional side-action rifles.

[0009] Therefore, it can be seen that a need yet exists for an improved muzzle-loading firearm with convenient access to the breech for replacing percussion caps and for cleaning. It would be further desirable to minimize or eliminate any additional overall length of a rifle that results from inline placement of the firing mechanism and primer loading action at the breech. It is to the provision of a muzzle-loading firearm meeting these and other needs that the present invention is primarily directed.

SUMMARY OF THE INVENTION

[0010] The present invention is an improved muzzle-loading firearm and includes a pivoting firing mechanism set that is pivotally attached to the barrel to allow it to swing down and provide free access to the breech plug in such a way that the percussion cap or primer can be replaced easily. The pivotal range of motion of the pivoting firing mechanism (a pivot block or falling block) allows easy access to the percussion cap in order to replace it, as well as to the breech plug, so it can be disassembled and cleaned out. As used herein, the terms "percussion cap" or "primer" include standard percussion caps as well as 209 shotgun primers and other ignition sources for muzzle-loading firearms.

[0011] Generally described, the present invention is an improved muzzle-loading firearm that has a pivotally attached firing mechanism (pivot block) and includes a mechanism for providing a positive prevention of unwanted movement from a blocked position to an unblocked position. The invention preferably also prevents inadvertent tripping of the firing mechanism when the pivot block is swung down to its unblocked position.

[0012] One example of the present invention is a muzzle-loading firearm including a barrel and a breach plug situated in a rear end of the barrel and adapted to receive a primer. A pivot block is mounted for pivotal motion relative to the barrel and has a firing mechanism mounted thereto, the firing mechanism including a striker for striking the primer, a hammer for driving the striker, and a trigger for tripping the

hammer. The pivot block is adapted for pivotal movement between a blocked position for firing and an unblocked position for providing access to the breech plug for removing a spent primer and replacing it with a fresh primer. Further, a trigger guard preferably is pivotally mounted to the pivot block for movement between three positions: (1) a locked position locking the pivot block in its blocked position; (2) an unlocked, blocked position in which the pivot block is still in its blocked position, but the pivot block is unlocked and ready to be moved therefrom; and (3) an unlocked, unblocked position in which the pivot block has been unblocked, providing access to the breech plug. Preferably, rotation of the trigger guard from the unlocked, blocked position to the unlocked, unblocked position causes the pivot block to move from its blocked position to its unblocked position. Preferably, initial rotation of the trigger guard from its locked position does not move the pivot block, but only unlocks it, and continued rotation of the trigger guard does move the pivot block.

[0013] Preferably, the trigger guard is held in its locked, blocked position by a spring clamp. An advantage of the spring clamp arrangement is that it tends to hold the trigger guard in its locked, blocked position, but does not apply a biasing force biasing the trigger guard against movement from the unlocked, blocked position toward the unlocked, unblocked position, thereby making it relatively easy to move the pivot block to its unblocked position. Alternatively, the trigger guard can be biased toward its locked, blocked position by a biasing spring.

[0014] Preferably, to prevent unwanted movement of the pivot block from its blocked position to its unblocked position, the trigger guard engages a structural barrier to prevent the pivot block from making this unwanted/unintended movement. To free the pivot block for movement, the trigger guard preferably is moved clear of the barrier, thereby allowing the pivot block to be moved, as by further rotation of the trigger guard or by some other mechanism or technique.

[0015] In another example embodiment of the present invention, the muzzle-loading firearm has a barrel and a pivoting firing mechanism. The barrel includes a

breach plug, which is inserted substantially at the back end of the barrel, a trigger guard blocking axle, and a pivoting junction axle. The pivoting firing mechanism includes a lineal striker, which is substantially in line with the breach plug and substantially at the rear end of the barrel, and a lineal striker spring, which is
5 substantially between the striker and the breach plug. The firing mechanism also includes a hammer, a hammer spring, a trigger, a trigger spring, and a trigger guard. The hammer preferably includes: a strike end, which is substantially behind the lineal striker and rotationally coupled to the firing mechanism for pivotal impact against the striker when fired; a middle portion having a hammer protuberance and a set back
10 uncocking support; and a hammer lever portion which includes a hammer safety notch and a hammer cocked notch. The firing mechanism preferably also includes: a hammer spring in contact at a first end to the hammer protuberance, a trigger spring, a trigger, and a trigger guard. The trigger preferably includes a trigger uncocked lever, a trigger shooting lever and a trigger safety lever. Additionally the trigger guard
15 includes a pivot-guiding notch, wherein the trigger guard blocking axle is slidingly located within the pivot-guiding notch. In this example embodiment, the combination of the pivot-guiding notch and the trigger guard blocking axle limits the pivoting of the firing mechanism with respect to the barrel. Preferably the pivot-guiding notch is substantially an "L"-shaped notch and when the firing mechanism pivots away from the
20 barrel, the pivot is to a sufficient degree as to allow for sufficient clearance for a percussion cap. It is preferable that the trigger guard has a trigger guard safety lever so that when the firing mechanism pivots away from the barrel, the trigger guard safety lever is aligned with the trigger safety lever, thereby preventing substantial movement of the trigger. It is also preferable that when the trigger uncocked lever is substantially
25 contacting the hammer cocked notch, the trigger spring is pre-loaded. Conversely, after shooting the firearm, the firearm is preferably in a post-shooting position where the hammer strike portion remains substantially in contact with the lineal striker. It is preferable that when the firearm is in the post-shooting position, the trigger guard

safety lever is positioned in a manner in relation to the trigger safety lever to substantially prevent the rotation of the firing mechanism.

[0016] In yet another example embodiment of the present invention the muzzle-loading firearm has a barrel with a breach plug inserted substantially at the back end of the barrel, a blocking axle and a pivoting axle. The firearm also has a pivoting firing mechanism that has a trigger, a trigger spring, a hammer, a hammer spring, a lineal striker and a striker spring. It is preferable for the trigger guard to have a guiding notch and to have the firing mechanism be pivotally attached at the pivoting axle and the firing mechanism slide within the guiding notch at the blocking axle. It is preferable for the guiding notch to be an "L"-shape notch that has a first portion and a second portion. When the firing mechanism slides along the first portion of the notch, the firing mechanism is unblocked and when the firing mechanism slides along the second portion the lineal striker of the firing mechanism moves away from the barrel of the firearm and provides sufficient clearance for insertion of a percussion cap between the striker and the barrel. It is also preferable for the firing mechanism of the firearm to have a base, which in turn, has a base-hammer protuberance. Additionally the hammer preferably has a hammer protuberance and between these two protuberances is the hammer spring, when the hammer is uncocked, the hammer spring is preferably pre-loaded due to contact of the one end of the spring 48 against the protuberance 45 and the other end of the spring 48 against the protuberance 74. It is also preferable that when the hammer is in a post-shooting position, the hammer return to the uncocked position by action of the spring 48. The trigger spring is then loaded with sufficient force to force the return of the trigger safety lever to the hammer safety notch, thereby returning the hammer to the un-cocked position.

[0017] Another example embodiment of the present invention is a firearm with a barrel having a pivot axle and a blocking axle, a firing mechanism with a guiding notch pivotally attached at the pivot axle, wherein the guiding notch directs the pivoting action of the firing mechanism. As noted, it is preferable that the notch is substantially

"L"-shaped. It is also preferable for the firing mechanism to have a trigger with a safety notch, and a trigger guard with a safety lever. Then, as the "L"-shaped notch has a first and a second portion, when the firing mechanism glides between the first and the second portion, the trigger safety notch and the trigger safety lever substantially align and prevent the pulling of the trigger. It is also preferable for the barrel to have an open and a substantially closed end, and for the firing mechanism to further have a lineal striker. As before, the "L"-shaped notch can have a first portion and a second portion; so that when the firing mechanism is sliding in the first portion, the linear striker and the closed end of the barrel are substantially aligned; and when the firing mechanism is in the second portion, there is clearance between the striker and the closed end of the barrel to allow for use of a percussion cap between the striker and the closed end of the barrel.

[0018] These and other features and advantages of the present invention will be apparent to those skilled in the art in view of the description and appended drawing figures herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a side view of an example of a muzzle-loading firearm of the present invention, showing its pivoting firing mechanism in a closed or uncocked position, where the hammer is also not cocked.

[0020] FIG. 2 is a side view of the pivoting firing mechanism of FIG. 1, showing the pivoting mechanism set unlocked and ready to be unblocked.

[0021] FIG. 3 is a side view of the pivoting firing mechanism of FIG. 1, showing the pivoting mechanism set totally unblocked (swung down).

[0022] FIG. 4 is a side view of the pivoting firing mechanism of FIG. 1, showing the pivoting mechanism set closed or blocked and the hammer in a cocked position.

[0023] FIG. 5 is a side view of the pivoting firing mechanism of FIG. 1, showing the pivoting mechanism set closed or blocked and showing the post-shooting hammer position.

5 [0024] FIG. 6 is a side view of an example of a muzzle-loading firearm of the present invention in a second preferred form, showing its pivoting firing mechanism in a closed or post-shooting position, where the hammer is also not cocked.

[0025] FIG. 7 is a side view of the pivoting firing mechanism of FIG. 6, showing the pivoting mechanism set unlocked and ready to be unblocked.

10 [0026] FIG. 8 is a side view of the pivoting firing mechanism of FIG. 6, showing the pivoting mechanism set totally unblocked (swung down).

[0027] FIG. 9 is a side view of the pivoting firing mechanism of FIG. 6, showing the pivoting mechanism set closed or blocked and the hammer in a cocked position.

15 [0028] FIG. 10 is a side view of the pivoting firing mechanism of FIG. 6, showing the pivoting mechanism set closed or blocked and showing the uncocked hammer position.

[0029] FIG. 11 is a perspective, partially exploded view of the pivoting firing mechanism of FIG. 6.

20 [0030] FIG. 12 is a series of side views of the pivoting firing mechanism of FIG. 6, showing the pivoting mechanism in use and depicting the movement of the various parts thereof.

DETAILED DESCRIPTION OF THE EMBODIMENTS

25 [0031] The present invention may be understood more readily by reference to the following detailed description of the invention taken in connection with the accompanying drawing figures, which form a part of this disclosure. It is to be understood that this invention is not limited to the specific devices, methods, conditions

or parameters described and/or shown herein, and that the terminology used herein is for the purpose of describing particular embodiments by way of example only and is not intended to be limiting of the claimed invention. Also, as used in the specification including the appended claims, the singular forms "a," "an," and "the" include the plural, and reference to a particular numerical value includes at least that particular value, unless the context clearly dictates otherwise. Ranges may be expressed herein as from "about" or "approximately" one particular value and/or to "about" or "approximately" another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent "about" or the like, it will be understood that the particular value forms another embodiment.

[0032] As shown in **FIG. 1**, which is a lateral view of an example of the present invention in a closed or uncocked position, a muzzle-loading firearm **90** is shown (with some portions of the stock and some portions of the barrel omitted for clarity). The firearm **90** preferably has a pivoting firing mechanism **10**, a barrel **20** and a stock **80**. The barrel **20** has a front end (not shown) and a back end. At the back end of the barrel **20** a breech plug **22** is inserted. The barrel **20** also includes a pivoting junction axle **75** and a blocking axle **64**. The stock **80** is attached at one or more points (not shown) to the barrel **20**.

[0033] The firing mechanism **10** preferably includes a lineal striker or firing pin **30** and a striker spring **32**. As shown, when in the closed position, the striker **30** is aligned with the breech plug **22**, and the striker spring is located between the striker **30** and the breech plug **22**, to ensure the return of the striker **30** to the position shown in **FIG. 1** after shooting the firearm **90**.

[0034] The firing mechanism **10** preferably also includes a hammer **40** and a hammer spring **42**. The hammer **40** has a strike portion **43** that, when the hammer is released forward upon firing the firearm **90**, contacts the striker **30**, discussed above.

The hammer **40** preferably also has a shooting support **44** which act as a pushing support for the hammer. A hammer protuberance **45** is in contact with a first end of the hammer spring **42**. The hammer **40** also includes a hammer safety notch **46** and a hammer cocked notch **47**, which are also discussed subsequently. Finally, the
5 hammer **40** includes a setback uncocking support **48**, which is also discussed subsequently.

[0035] The firing mechanism **10** preferably also includes a base **70** which has a base-hammer protuberance **74**, which is in contact with a second end of the hammer spring **42**. A trigger **50** is preferably included within the firing mechanism **10**, which
10 includes a trigger uncocked lever **52**, a trigger shooting lever **54** and a trigger safety lever **56**. A trigger spring **58** is positioned so as to force the trigger levers **52-54** toward the hammer notches **46-47**. When in the closed and uncocked position, the trigger uncocked lever **52** is in contact with hammer safety notch **46**, thereby preloading hammer spring **48** between the hammer protuberance **45** and the base-hammer
15 protuberance **74**, due to engagement of one end of spring **48** against protuberance **45** and the other end of spring **48** against protuberance **74**.

[0036] The firing mechanism **10** preferably also includes a trigger guard **60** which has an "L"-shaped notch or track **62** and a trigger guard safety lever **66**. The firing mechanism **10** is pivotally attached to the barrel **20** at the pivoting junction axle
20 **75** and the blocking axle **64** is slidably engaged within the "L"-shaped notch or track **62**.

[0037] As shown in **FIG. 2**, when the firing mechanism **10** is unlocked by sliding the firing mechanism **10** about the blocking axle **64** so that it is between the first and the second positions of the "L"-shaped notch **62**, the trigger guard safety lever **66**
25 aligns with the trigger safety lever **56**, thereby preventing the movement of the trigger levers **52-54** away from hammer notches **46-47**. This effectively prevents the trigger from being tripped when the pivoting firing mechanism is in an unblocked position. In fact, it also prevents the trigger from being tripped when the firing mechanism is

unlocked but still blocked, as shown in this figure. It should also be noted that in the present example the trigger guard **60** is substantially closer to the trigger **50** when in this position as compared to the position in **FIG. 1**.

5 **[0038]** Now turning to **FIG. 3**, which depicts the pivoting firing mechanism **10** when completely unblocked, by slidingly moving the "L" shaped notch **62** about the blocking axle **64** so that blocking axle **64** is positioned at the end of the longer, second portion of the notch **62**, it can be seen that there is essentially complete clearance for placement of a percussion cap (not shown) in the breech plug **22**. Additionally, the striker **30** is drawn back sufficiently to allow for ease of cleaning.

10 **[0039]** Upon examining **FIG. 4** we can see the lateral view of the firing mechanism **10** of **FIG. 1** when in the closed and cocked position. The hammer **40** is drawn back, fully loading the hammer spring **42**. The hammer is held in place by the hammer cocked notch **47** contacting the trigger shooting lever **54**. In this position the trigger guard is locked closed by abutment of trigger guard safety lever **66** against
15 trigger safety lever **56**. Upon pulling the trigger **50** the trigger shooting lever **54** disengages from the hammer cocked notch **47**, and due to the loading of the hammer spring **42**, the hammer strike portion **43** rotates toward the striker **30**.

20 **[0040]** As shown in **FIG. 5**, which is a lateral view of the firing mechanism **10** of **FIG. 1** in the closed position just after shooting, the hammer striker portion **43** comes in contact with the striker **30** in a rapid fashion which has sufficient kinetic energy to cause the compression of the striker spring **32**. If a percussion cap, or the like, had been placed between the striker **30** and the breech plug **22** in the barrel **20**, the percussion cap fires, igniting any gunpowder charge located on the opposite (forward) side of the breech plug **22**.

25 **[0041]** It should be noticed that the setback uncocking support **48** is in contact with the second portion of the hammer spring **42** which provides a loading of the hammer **40** to return to the uncocked position, as shown in **FIG. 1**. Additionally the

trigger spring **52** is loaded, and provides a loading of the trigger uncocked lever **52** to return to the uncocked position as shown in **FIG. 1**. Therefore, after shooting the firearm **90**, the firing mechanism **10** returns to the uncocked position as shown in **FIG. 1**.

5 **[0042]** It should be understood that when the user wishes to perform a complete cleaning of the firing mechanism **10**, the stock **80** can be taken off of the barrel **20** by unscrewing the bolt(s) (not shown) that connect(s) these parts together. The firing mechanism **10**, which preferably is securely joined to the barrel **20** by the pivoting axle **75** and blocking axle **64**, can be accessible for cleaning purposes.

10 **[0043]** It should also be appreciated that the present invention also substantially eliminates or minimizes the dangers of blowback gas reaching the face of the shooter, as the breech plug **22** is axially assembled in the barrel **20**, and when the firing mechanism **10** is not pivoted down and unblocked, the pivoting firing mechanism **10** completely closes off the rear portion of the barrel **20**. This closing is achieved in part
15 by the base **70** of the firing mechanism **10** and the location of the lineal striker **30**, which not only decreases the risk of blowback gas reaching the shooter, it also prevents debris and rainwater from reaching the percussion cap.

20 **[0044]** While it is preferable that the trigger guard **60** "guard" the trigger **50**, the trigger guard **60** need not be an actual guard, but the term in the present specification includes any structure or means that allows the user of the firearm **90** to pivot the firing mechanism **10**. This can include, for example, a knob, handle or the like. It should also be noted that the trigger guard need not be a single piece or rigid piece of metal, and some internal "bending" could be allowed to facilitate the blocking and unblocking of the trigger guard **60**, and therefore allow for the controlled pivoting of the firing
25 mechanism **10** as discussed herein. The trigger guard can be formed from a single piece of metal or as multiple parts.

[0045] Additionally, when using the term “barrel” **20** in the present specification, the term includes not only the “tube” or bored out rod for which the bullets, or the like, are placed, but also the fixed periphery parts including, without limitation, the pivoting junction axle **75** and the blocking axle **64**.

5 **[0046]** Referring now to **FIGS. 6-12**, the reader’s attention is directed to the second preferred form of the invention similar to the first in many respects. However, in this second embodiment (in comparison to the first described embodiment), the mechanism guiding movement of the trigger guard relative to the pivot block has been simplified, the biasing spring biasing the trigger guard toward its locked position has
10 been replaced with a spring clamp, and the firing pin has been refined.

[0047] **FIG. 6**, which is a lateral view of an example of the present invention with a pivoting firing mechanism in a closed or uncocked position, shows a firearm **190** which preferably has a firing mechanism **110**, a barrel **120** and a stock **180**. The barrel **120** has a front end (not shown) and a back end. At the back end of the barrel **120** a
15 breech plug **122** is inserted therein. The stock **180** is attached at one or more points (not shown) to the barrel **120**.

[0048] Like the first embodiment, the firing mechanism **110** preferably includes a lineal striker or firing pin **130** and a striker spring **132**. As shown, when in the closed
20 position, the striker **130** is aligned with the breech plug **122**, and the striker spring is located between the striker **130** and the breech plug **122**, to ensure return of the striker **130** to the position shown in **Fig. 6** after shooting the firearm **190**.

[0049] As in the first embodiment, the firing mechanism **110** preferably also includes a hammer **140** and a hammer spring **142**. The hammer **140** has a strike
25 portion that contacts the striker **130** when the hammer is released forward upon firing the firearm **190**.

[0050] Like the first embodiment, the firing mechanism **110** preferably also includes the various parts that operate and selectively lock and unlock the trigger **150**. A description of all those parts need not be repeated here.

[0051] The firing mechanism **110** preferably also includes a trigger guard **160**.
5 The trigger guard **160** is pivotally mounted to a base **170** at a pivot axle **172**. In turn, the base **170** is pivotally mounted to the barrel **120** at axle **174**. The trigger guard **160** includes a pawl or foot **162** which selectively engages (or disengages from) a fixed barrier or dog **164**. When the trigger guard **160** is in the position shown here in **FIG. 6**, the foot **162** engages the fixed barrier **164**, thereby preventing the base **170** from
10 rotating from the position depicted. Thus, the foot **162** engaging the fixed barrier **164** effectively locks the base **170** (and the rest of the firing mechanism **110**) in this locked, blocked configuration shown in this figure. Advantageously, the engagement between foot **162** and the fixed barrier **164** is aligned with the axle **172** such that unwanted movement of the trigger guard **160** from this locked position is prevented. This feature
15 effectively prevents forces resulting from the combustion of the powder from unwantedly forcing the pivoting firing mechanism **110** open (toward the unblocked configuration). This helps to maintain a good seal at the rear of breech plug **122**, thereby helping to keep combustion gases from venting in uncontrolled paths. To hold the trigger guard **160** in this locked position of **FIG. 6**, a spring clamp **169** is provided.
20 The spring clamp **169** has a crook **168** formed in one end thereof for engaging a notch or detent **161** formed in part of the trigger guard **160**. This spring clamp/detent arrangement advantageously holds the trigger guard **160** rather securely against inadvertent movement from the locked position of **FIG. 6**. However, the spring clamp/detent can be easily overcome by the user rotating the trigger guard **160** in the
25 direction of direction arrow **163** by applying a little downward force on the handle end **167** of the trigger guard **160**.

[0052] As shown in **FIG. 7**, when the pivoting firing mechanism **110** is unlocked by rotating the trigger guard **160** about the pivot axle **172** so that it is in the position

depicted, the trigger guard safety lever **166** aligns with the top portion **156** of trigger **150**, thereby preventing the trigger from being pulled. Thus, as shown in **FIG. 7**, the trigger guard **160** is unlocked, which has the effect of locking the trigger **150**. Also, it should be noted that from this unlocked position, the trigger guard **160** can be rotated further in the direction of direction arrow **163** with relative ease. This is so because with the spring clamp **169** no longer engaging the detent **161**, the spring clamp exerts no force on the trigger guard (unlike the first embodiment described above where the return spring constantly biases the trigger guard toward a closed or blocked position). Thus, continued downward force on the handle end **167** of the trigger guard **160** causes it (and the pivoting firing mechanism **110**) to move from the position of **FIG. 7** to that of **FIG. 8**. This movement of the entire firing mechanism **110** is facilitated by the foot **162** clearing the fixed barrier **164** and being aligned with a curved pathway or curved slot **165**. Thus, as the base **170** is rotated about the axle **174**, the foot **162** rides in the curved slot **165**.

[0053] **FIG. 8** depicts the firing mechanism **110** when completely unblocked, with the foot **162** well within the curved slot **165**. When in this position, it can be seen that there is essentially complete clearance for placement of a percussion cap (not shown) in the breech plug **122**. When the firing mechanism **110** is swung down, the hammer cannot be cocked until the action is closed.

[0054] Upon examining **FIG. 9** we can see the lateral view of the firing mechanism **110** of **FIG. 6** when in the closed and cocked position. The hammer **140** is drawn back, fully loading its hammer spring. To move the firing mechanism **110** to this position from that of **FIG. 8**, the user would simply rotate the firing mechanism upwardly by pulling up on the trigger guard, such as on the handle portion **167** thereof, until the detent is captured by the crook formed in the spring clamp, and cock the hammer.

[0055] **FIG. 10** is a lateral view of the firing mechanism **110** of **FIG. 6** in the closed position just after shooting, wherein the hammer striker portion comes in contact

with the striker in a rapid fashion and which has sufficient kinetic energy to cause the compression of the striker spring. If a percussion cap, or the like, had been placed between the striker and the breach plug **122** in the barrel **120**, the cap would fire, igniting any gunpowder charge located on the opposite side of the breech plug **122**.

5 **[0056]** **FIG. 11** is an exploded, perspective view of selected portions of the pivoting firing mechanism **110** and shows the two-piece base **170** which is pivotally mounted to the barrel (see **FIG. 6** for this pivotal mounting). The trigger guard **160** is pivotally mounted within the base **170** about the pivot axle **172**. The trigger guard includes the detent **161** to be captured at times by the spring clamp **169**. The spring
10 clamp **169** is fitted over a boss formed in the base **170** and includes the previously described crook **168**.

[0057] **FIG. 12** is a sequential series of side views showing the progression of the various parts in use as follows (from top to bottom):

- (a) post-firing, with the trigger guard unlocked;
- 15 (b) trigger guard and the rest of the firing mechanism unblocked for cleaning and/or reloading;
- (c) firing mechanism returned to blocked position, but hammer not cocked;
- (d) firing mechanism blocked, hammer cocked - - ready for firing; and
- (e) post-firing, with firing mechanism blocked and trigger guard locked.

20 **[0058]** In view of the foregoing, it will be appreciated that the present invention avoids many of the drawbacks of prior muzzle-loading firearms by allowing for significant pivoting of the firing mechanism in relation to the barrel. The specific techniques and structures employed by the invention to improve over the drawbacks of the prior art and to accomplish the advantages described above will become
25 apparent from the above detailed description of the embodiments of the invention and

the appended drawings and claims. It should be understood that the foregoing relates only to the exemplary embodiments of the present invention, and that numerous changes may be made therein without departing from the spirit and scope of the invention as defined by the following claims.

5

10